

Multi-Conductor Unshielded Cable

Audio Control Cable UL CM, CSA AWM CMG

Conductors: Stranded Tin-Plated Copper
Insulation: SR-PVC
Jacket: Gray PVC
Construction: Conductors Cabled
Temperature Rating: UL 80°C (UL 60°C under 30 mil jacket thickness), CSA 105°C
Operating Voltage: 300 Volts UL, 600 Volts CSA
Applications: For point to point wiring of computers, control systems, electronic apparatus and panels.
Approvals: UL, CM, CMR
 CSA AWM II A/B, CMG FT4



TEVELEC NUMBER	No. of Conds.	AWG Size	Stranding	Nominal Insulation	Nominal Jacket	Nominal O.D.	Color Chart	Weight Lbs/1000'
T5202	2	24	7	.009	.015	.125	1	10
T5203	3	24	7	.009	.015	.130	1	12
T5204	4	24	7	.009	.015	.145	1	16
T5205	5	24	7	.009	.023	.155	1	20
T5206	6	24	7	.009	.023	.174	1	27
T5207	7	24	7	.009	.023	.188	1	31
T5208	8	24	7	.009	.023	.200	1	34
T5209	9	24	7	.009	.023	.212	1	38
T5210	10	24	7	.009	.023	.225	1	43
T5402	2	22	7	.010	.015	.131	Blk/Red	12
T5403	3	22	7	.010	.015	.139	Blk/Red/Grn	14
T5404	4	22	7	.010	.015	.152	1	18
T5405	5	22	7	.010	.015	.160	1	22
T5406	6	22	7	.010	.023	.192	1	32
T5407	7	22	7	.010	.023	.203	1	34
T5408	8	22	7	.010	.023	.215	1	38
T5409	9	22	7	.010	.023	.225	1	42
T5410	10	22	7	.010	.023	.234	1	46
T5411	12	22	7	.010	.023	.251	1	54
T5412	15	22	7	.010	.023	.275	2	64
T5413	20	22	7	.010	.030	.323	2	87
T5414	25	22	7	.010	.030	.354	2	105
T5415	30	22	7	.010	.030	.381	2	125
T5416	40	22	7	.010	.030	.432	2	160
T5417	50	22	7	.010	.035	.493	2	195