

# Electrical Cable

## Portable Cords SJOOW

**Conductors:** Stranded Bare Copper  
**Insulation:** Oil resistant thermoset.  
**Jacket:** Black oil resistant thermoset.  
**Construction:** Conductors cabled with fillers.  
**Temperature Rating:** -40°C to +90°C  
**Color Code Chart:** Black, white, Green, Red.  
**Operating Voltage:** 300 Volts  
**Applications:** For use as portable power cord where voltage does not exceed 300 Volts and oil and water resistance is desirable.  
**Approvals:** UL & CSA SJOOW



TEVELEC NUMBER	No. of Conds.	AWG Size	Stranding	Nominal Insulation	Nominal O.D.	Weight Lbs/1000'	Current Amps
T35182	2	18	16	.030	.310	50	10
T35183	3	18	16	.030	.330	60	10
T35184	4	18	16	.030	.360	70	7
T35162	2	16	26	.030	.330	60	13
T35163	3	16	26	.030	.355	75	13
T35164	4	16	26	.030	.390	95	10
T35142	2	14	41	.030	.370	75	18
T35143	3	14	41	.030	.390	105	18
T35144	4	14	41	.030	.420	125	15
T35122	2	12	65	.030	.410	105	25
T35123	3	12	65	.030	.430	140	25
T35124	4	12	65	.030	.475	190	20
T35102	2	10	105	.045	.560	210	30
T35103	3	10	105	.045	.610	240	30
T35104	4	10	105	.045	.655	325	25