

Electrical Cable

Portable Cords SOOW

Conductors:	Stranded bare copper
Insulation:	Oil resistant thermoset rubber.
Jacket:	Black oil resistant thermoset rubber
Construction:	Insulated conductors cabled with fillers.
Temperature Rating:	-40°C TO +90°C
Color Code Chart:	Black, White, Green, Red
Operating Voltage:	600 Volts
Applications:	For use as power supply cable for portable appliances.
Approvals:	UL & CSA SOOW



TEVELEC NUMBER	No. of Conds.	AWG Size	Stranding	Nominal Insulation	Nominal O.D.	Weight Lbs/1000'	Current Amps
T38182	2	18	16	.030	.345	70	10
T38183	3	18	16	.030	.365	80	10
T38184	4	18	16	.030	.390	95	7
T38162	2	16	26	.030	.370	80	13
T38163	3	16	26	.030	.390	95	13
T38164	4	16	26	.030	.420	115	10
T38142	2	14	41	.045	.530	135	18
T38143	3	14	41	.045	.560	170	18
T38144	4	14	41	.045	.575	205	15
T38122	2	12	65	.045	.570	195	25
T38123	3	12	65	.045	.595	225	25
T38124	4	12	65	.045	.650	270	20
T38102	2	10	104	.045	.620	250	30
T38103	3	10	104	.045	.660	290	30
T38104	4	10	104	.045	.715	355	25
T38083	3	8	133	.060	.855	485	40
T38084	4	8	133	.060	.980	670	35
T38085	5	8	133	.060	1.075	790	28
T38063	3	6	133	.060	.980	700	55
T38064	4	6	133	.060	1.090	875	45
T38065	5	6	133	.060	1.200	1015	36
T38043	3	4	133	.060	1.140	920	70
T38044	4	4	133	.060	1.260	1150	60
T38045	5	4	133	.060	1.365	1400	48
T38023	3	2	133	.060	1.330	1355	95
T38024	4	2	133	.060	1.460	1690	80
T38025	5	2	133	.060	1.580	1960	64