

Electrical Cable

Portable Cables Type G or GGC

Conductors: Stranded bare copper
Insulation: EPDM
Jacket: CPE
Construction: Conductors cabled with fillers.
Temperature Rating: 90°C to -40°C
Color Code Chart: Black, white, red, orange
Operating Voltage: 600/2000 Volts
Applications: Heavy duty power supply cable for mobile or portable electrical equipment.
Approvals: ICEA S-68-526 NEMA WC-8, ICEA S-19-81 NEMA WC-3



TEVELEC NUMBER	No. of Conds.	AWG & Stranding	Ground Conds.	Nominal Insulation	Nominal O.D.	Weight Lbs/1000'	Current Amps
T52308	3	8/133	2-#10	.060	1.005	693	59
T52306	3	6/259	2-#10	.060	1.085	870	79
T52304	3	4/259	2-#8	.060	1.190	1260	104
T52303	3	3/329	2-#8	.060	1.250	1460	120
T52302	3	2-259	2-#7	.060	1.340	1650	138
T52301	3	1-259	2-#6	.080	1.510	2100	161
T52310	3	1/0-259	2-#5	.080	1.650	2550	186
T52320	3	2/0-259	2-#4	.080	1.750	3020	215
T52330	3	3/0-259	2-#3	.080	1.890	3660	249
T52340	3	4/0-259	2-#2	.080	2.040	4410	287
T52341	3	250-627	2-#2	.095	2.390	6060	320
T52342	3	300-741	2-#1	.095	2.560	6700	357
T52343	3	350-855	2-#1/0	.095	2.680	7400	394
T52344	3	400-988	2-#1/0	.095	2.820	8350	430
T52350	3	500-1235	2-#2/0	.095	3.030	10100	487
T52408	4	8/133	4-#12	.060	1.025	830	54
T52406	4	6/259	4-#12	.060	1.135	1030	72
T52404	4	4/259	4-#10	.060	1.270	1480	93
T52403	4	3/329	4-#10	.060	1.340	1830	106
T52402	4	2-259	4-#9	.060	1.480	2070	122
T52401	4	1-259	4-#8	.080	1.680	2660	143
T52410	4	1/0-259	4-#7	.080	1.790	3140	165
T52420	4	2/0-259	4-#6	.080	1.930	3780	192
T52430	4	3/0-259	4-#5	.080	2.070	4500	221
T52440	4	4/0-259	4-#4	.080	2.260	5520	255