

High Temperature Wire

FEP 200°C UL1371

Conductor: Solid or stranded tin-plated copper conductors
Insulation: Fluorinated ethylene propylene
Temperature Rating: 105°C
Operating Voltage: Not rated
Applications: For use in back panel areas of electronic equipment, such as computers and business machines where not subjected to mechanical abuse.
Approvals: UL AWM 1371



TEVELEC NUMBER	AWG Size	Stranding	Nominal Insulation	Nominal O.D.	Weight Lbs/1000'
T1433	30	1	.006	.022	.623
T1434	30	7	.006	.024	.719
T1435	28	1	.006	.025	.871
T1436	28	7	.006	.027	.989
T1437	28	19	.006	.027	1.03
T1438	26	1	.006	.036	1.21
T1439	26	7	.006	.039	1.43
T1440	26	19	.006	.039	1.52
T1441	24	1	.006	.040	1.70
T1442	24	7	.006	.044	2.11
T1443	24	19	.006	.044	2.11
T1444	22	1	.006	.045	2.5
T1445	22	7	.006	.050	3.05
T1446	22	19	.006	.050	3.09
T1447	20	1	.006	.052	3.8
T1448	20	7	.006	.058	4.57
T1449	20	19	.006	.058	4.67
T1450	18	1	.010	.060	6.4
T1451	18	7	.010	.068	7.2
T1452	18	19	.010	.069	7.48
T1455	16	19	.010	.076	9.75
T1458	14	19	.015	.099	16.4
T1460	12	19	.015	.118	24.8
T1461	10	19	.015	.144	35.1