

High Temperature Wire

ETFE

300 Volts 150°C UL1671, CSA AWM

Conductor: Tin-Plated Copper
Insulation: ETFE
Temperature Rating: 150°C
Operating Voltage: 300 Volts
Applications: Internal wiring of electronic components.
Approvals: UL1671 AWM 150°C 300 Volts
 CSA AWM I A/B 150°C 300 Volts



TEVELEC NUMBER	AWG Size	Stranding	Nominal Insulation	Nominal O.D.	Voltage Rating	Weight Lbs/1000'
T0327	24	19	.010	.044	300	2.2
T0328	22	19	.010	.050	300	3.3
T0329	20	19	.010	.059	300	4.9
T0330	18	19	.010	.068	300	7.2
T0331	16	19	.010	.077	300	9.5
T0332	14	19	.010	.090	300	15
T0333	12	19	.010	.109	300	21
T0334	10	19	.010	.133	300	35

ETFE

600 Volts 150°C UL1644, CSA AWM

Conductor: Tin-Plated Copper
Insulation: ETFE
Temperature Rating: 150°C
Operating Voltage: 600 Volts
Applications: Internal wiring of electronic components.
Approvals: UL1644 AWM 150°C 600 Volts
 CSA AWM I A/B 150°C 600 Volts



TEVELEC NUMBER	AWG Size	Stranding	Nominal Insulation	Nominal O.D.	Voltage Rating	Weight Lbs/1000'
T0290	24	19	.020	.064	600	4
T0291	22	19	.020	.070	600	5.2
T0292	20	19	.020	.079	600	7
T0293	18	19	.020	.088	600	9
T0294	16	19	.020	.097	600	12
T0295	14	19	.020	.110	600	17
T0296	12	19	.020	.129	600	24
T0297	10	37	.020	.153	600	38