

Hook-up & Lead Wire

UL1007, UL1569, CSA TR-64 300V 80°C 90°C 105°C

Conductor: Stranded or solid Tinned Copper
Insulation: PVC
Applications: Internal wiring of electrical or electronic equipment, panels and meters.
Approvals: UL1007 - 80C 300 Volts
 UL1569 - 105C 300 Volts
 CSA TR-64 - 90C 300 Volts
 Meets UL VW-1 Vertical Flame Test.
Packaging: 1000' Spools (305m)
 5,000' Spools (1525m)
 Bulk Spools or Drums



TEVELEC NUMBER	AWG Size	Stranding	Nominal Insulation	Nominal O.D.	Weight Lbs/1000'
T1008	24	1	.015	.052	2.50
T1010	22	1	.015	.057	3.50
T1015	18	1	.015	.077	7.80
T1009	24	7	.015	.056	2.60
T1011	22	7	.015	.062	3.65
T1014	20	10	.015	.069	5.45
T1016	18	16	.015	.078	7.90
T1018	16	26	.015	.092	10.50

UL1007, CSA TR-64 Prefused Conductor 300V 80°C 90°C

Conductor: Stranded Prefused Tinned Copper.
Insulation: PVC
Applications: Internal wiring of electrical or electronic equipment, panels and meters.
Approvals: UL1007 - 80C 300 Volts
 UL1569 - 105C 300 Volts
 CSA TR-64 - 90C 300 Volts
 Meets UL VW-1 Vertical Flame Test.
Packaging: 1000' Spools (305m)
 5,000' Spools (1525m)
 Bulk Spools or Drums



TEVELEC NUMBER	AWG Size	Stranding	Nominal Insulation	Nominal O.D.	Weight Lbs/1000'
T1021	24	7	.015	.057	3.00
T1022	22	7	.015	.063	4.05
T1023	20	7	.015	.069	5.80
T1024	18	7	.015	.077	8.50
T1025	16	7	.015	.091	9.50