

Military Wire

MIL-W-22759/7 600 Volts 200°C

Conductor: Stranded, Silver Plated Copper
Insulation: Extruded PTFE Reinforced with Abrasion-Resistant Mineral Fillers
Jacket: None
Temperature Rating: 200°C
Operating Voltage: 600 Volts
Specification: Conforms to the requirements of MIL-W-22759/7



TEVELEC NUMBER	AWG Size	Stranding	Nominal Insulation	Nominal O.D.	Voltage Rating	Military Number	Weight Lbs/1000'
T01600	24	19	.020	.062	600	M22759/7-24-X	3.8
T01601	22	19	.020	.073	600	M22759/7-22-X	5.4
T01602	20	19	.020	.082	600	M22759/7-20-X	7.3
T01603	18	19	.020	.096	600	M22759/7-18-X	9.9
T01604	16	19	.020	.102	600	M22759/7-16-X	13.0
T01605	14	19	.020	.112	600	M22759/7-14-X	17.9
T01606	12	19	.020	.134	600	M22759/7-12-X	25.7
T01607	10	37	.020	.158	600	M22759/7-10-X	38.0

MIL-W-22759/8 600 Volts 260°C

Conductor: Stranded, Nickel-Plated Copper
Insulation: Extruded PTFE Reinforced with Abrasion-Resistant Mineral Fillers
Jacket: None
Temperature Rating: 260°C
Operating Voltage: 600 Volts
Specification: Conforms to the requirements of MIL-W-22759/8



TEVELEC NUMBER	AWG Size	Stranding	Nominal Insulation	Nominal O.D.	Voltage Rating	Military Number	Weight Lbs/1000'
T01620	24	19	.020	.062	600	M22759/8-24-X	3.8
T01621	22	19	.020	.073	600	M22759/8-22-X	5.4
T01622	20	19	.020	.082	600	M22759/8-20-X	7.3
T01623	18	19	.020	.096	600	M22759/8-18-X	9.9
T01624	16	19	.020	.102	600	M22759/8-16-X	13.0
T01625	14	19	.020	.112	600	M22759/8-14-X	17.9
T01626	12	19	.020	.134	600	M22759/8-12-X	25.7
T01627	10	37	.020	.158	600	M22759/8-10-X	38.0