

Military Wire

MIL-W-22759/11 600 Volts 200°C

Conductor: Stranded, Silver Plated Copper
Insulation: Extruded PTFE
Jacket: None
Temperature Rating: 200°C
Operating Voltage: 600 Volts
Specification: Conforms to the requirements of MIL-W-22759/11



TEVELEC NUMBER	AWG Size	Stranding	Nominal Insulation	Nominal O.D.	Voltage Rating	Military Number	Weight Lbs/1000'
T01680	28	7	.010	.033	600	M22759/11-28-X	1.18
T01681	26	19	.010	.038	600	M22759/11-26-X	1.71
T01682	24	19	.010	.043	600	M22759/11-24-X	2.37
T01683	22	19	.010	.049	600	M22759/11-22-X	3.37
T01684	20	19	.010	.058	600	M22759/11-20-X	5.07
T01685	18	19	.010	.068	600	M22759/11-18-X	7.45
T01686	16	19	.010	.075	600	M22759/11-16-X	9.31
T01687	14	19	.010	.090	600	M22759/11-14-X	14.17
T01688	12	19	.010	.111	600	M22759/11-12-X	21.03
T01689	10	37	.010	.138	600	M22759-11-10-X	32.03

MIL-W-22759/12 600 Volts 260°C

Conductor: Stranded, Nickel-Plated Copper
Insulation: Extruded PTFE
Jacket: None
Temperature Rating: 260°C
Operating Voltage: 600 Volts
Specification: Conforms to the requirements of MIL-W-22759/12



TEVELEC NUMBER	AWG Size	Stranding	Nominal Insulation	Nominal O.D.	Voltage Rating	Military Number	Weight Lbs/1000'
T01700	28	7	.010	.033	600	M22759/12-28-X	1.18
T01701	26	19	.010	.038	600	M22759-12-26-X	1.71
T01702	24	19	.010	.043	600	M22759/12-24-X	2.37
T01703	22	19	.010	.049	600	M22759/12-22-X	3.37
T01704	20	19	.010	.058	600	M22759/12-20-X	5.07
T01705	18	19	.010	.068	600	M22759/12-18-X	7.45
T01706	16	19	.010	.075	600	M22759/12-16-X	9.31
T01707	14	19	.010	.090	600	M22759/12-14-X	14.17
T01708	12	19	.010	.111	600	M22759/12-12-X	21.03
T01709	10	37	.010	.139	600	M22759/12-10-X	32.03