

Military Wire

MIL-W-22759/13 600 Volts 135°C

Conductor: Stranded, Tin-Plated Copper
Insulation: Extruded FEP
Jacket: .005" Extruded Polyvinylidene Fluoride
Temperature Rating: 135°C
Operating Voltage: 600 Volts
Specification: Conforms to the requirements of MIL-W-22759/13



TEVELEC NUMBER	AWG Size	Stranding	Nominal Insulation	Nominal O.D.	Voltage Rating	Military Number	Weight Lbs/1000'
T01722	24	19	.013	.049	600	M22759/13-24-X	2.6
T01723	22	19	.011	.051	600	M22759/13-22-X	3.6
T01724	20	19	.011	.061	600	M22759/13-20-X	5.2
T01725	18	19	.011	.071	600	M22759/13-18-X	7.5
T01726	16	19	.011	.078	600	M22759/13-16-X	9.5
T01727	14	19	.011	.091	600	M22759/13-14-X	14.8
T01728	12	19	.011	.111	600	M22759/13-12-X	21.8
T01729	10	37	.010	.138	600	M22759-13-10-X	34

MIL-W-22759/14 600 Volts 135°C

Conductor: Stranded, Tin-Plated Copper
Insulation: Extruded FEP
Jacket: .003" Extruded Clear Polyvinylidene Fluoride
Temperature Rating: 135°C
Operating Voltage: 600 Volts
Specification: Conforms to the requirements of MIL-W-22759/14



TEVELEC NUMBER	AWG Size	Stranding	Nominal Insulation	Nominal O.D.	Voltage Rating	Military Number	Weight Lbs/1000'
T01741	26	19	.009	.037	600	M22759/14-26-X	1.6
T01742	24	19	.009	.042	600	M22759/14-24-X	2.3
T01743	22	19	.009	.048	600	M22759/14-22-X	3.3
T01744	20	19	.009	.056	600	M22759/14-20-X	4.8
T01745	18	19	.009	.066	600	M22759/14-18-X	7.3
T01746	16	19	.009	.071	600	M22759/14-16-X	8.8
T01747	14	19	.009	.087	600	M22759/14-14-X	13.7
T01748	12	19	.009	.107	600	M22759/14-12-X	21.2