

Multi-Conductor Shielded Cable

Audio Control Cable UL CM CSA AWM CMG

Conductors: Stranded Tin-Plated Copper
Insulation: PVC
Shield: Aluminum/Polyester Foil Shield with Tinned Copper Drain Wire
Jacket: Premium Grade PVC
Construction: Conductors Cabled.
Temperature Rating: UL 80°C, CSA 105°C
Operating Voltage: CSA 600 Volts, UL 300 Volts
Applications: For point to point wiring of computers, control systems, electronic apparatus and panels where shielding is required.
Approvals: UL CM CSA AWM CMG FT4



TEVELEC NUMBER	No. of Conds.	AWG Size	Stranding	Nominal Insulation	Nominal Jacket	Nominal O.D.	Color Chart	Weight Lbs/1000'
T5525	2	20	7	.010	.020	.162	Blk/Red	20
T5526	3	20	7	.010	.023	.176	1	28
T5527	4	20	7	.010	.023	.191	1	34
T5528	5	20	7	.010	.023	.199	2	39
T5530	7	20	7	.010	.023	.217	2	51
T5532	9	20	7	.010	.023	.255	2	59
T5534	12	20	7	.010	.023	.287	2	75
T5535	15	20	7	.010	.030	.322	2	93
T5536	19	20	7	.010	.030	.354	2	114
T5537	25	20	7	.010	.030	.396	2	142
T5550	2	18	16	.012	.023	.197	Blk/Red	33
T5551	3	18	16	.012	.023	.209	1	39
T5552	4	18	16	.012	.023	.228	1	47
T5553	5	18	16	.012	.023	.233	2	51
T5554	6	18	16	.012	.023	.251	2	58
T5555	7	18	16	.012	.023	.267	2	66
T5557	9	18	16	.012	.023	.296	2	82
T5559	12	18	16	.012	.030	.355	2	109
T5560	15	18	16	.012	.030	.388	2	140
T5561	19	18	16	.012	.030	.431	2	171
T5562	25	18	16	.012	.035	.486	2	214
T5563	30	18	16	.012	.035	.541	2	275
T5564	40	18	16	.012	.050	.620	2	354
T5565	50	18	16	.012	.050	.744	2	421