

Multi-Pair Cable

Overall Foil Shield UL CM, CSA AWM CMG

Conductors: Tin-Plated Copper
Insulation: Premium PVC
Shield: Aluminum/Mylar Foil with Drain Wire
Jacket: PVC
Construction: Conductors Paired, Pairs Cabled and shielded overall
Temperature Rating: 105°C
Color Code Chart: 3, 3R
Operating Voltage: 300 Volts, 600 Volts
Applications: Computer Interconnection, Data Transmission, Control Circuits, Industrial Equipment Control, Suitable for EIA RS-232 applications.
Approvals: UL 80°C 300 Volts, CSA CMG FT4 105°C 600 Volts



TEVELEC NUMBER	No. of Pairs	AWG Size	Stranding	Nominal Insulation	Nominal Jacket	Nominal O.D.	Weight Lbs/1000'
T2801	1	24	7	.010	.030	.150	15
T2802	2	24	7	.010	.030	.216	22
T2803	3	24	7	.010	.030	.227	27
T2804	4	24	7	.010	.030	.246	32
T2806	6	24	7	.010	.030	.281	44
T2808	8	24	7	.010	.030	.307	55
T2809	9	24	7	.010	.030	.330	61
T2810	10	24	7	.010	.030	.337	65
T2812	12	24	7	.010	.030	.350	74
T2815	15	24	7	.010	.030	.385	89
T2819	19	24	7	.010	.030	.412	107
T2825	25	24	7	.010	.030	.481	136