

# Multi-Pair Cable

## Overall Foil Shielded Low Capacitance UL CM, CSA CMG

**Conductors:** Tin-Plated Copper  
**Insulation:** Cellular Polyolefin  
**Shield:** Aluminum/Mylar Foil with Drain Wire  
**Jacket:** PVC  
**Construction:** Conductors Paired, Pairs Cabled and shielded overall  
**Temperature Rating:** 80°C  
**Color Code Chart:** 5  
**Operating Voltage:** 150 Volts  
**Applications:** Computer Interconnection, Data Transmission, Control Circuits, Industrial Equipment Control, Suitable for EIA RS-232 applications.  
**Approvals:** UL Style 2919 AWM, CSA CMG FT4



TEVELEC NUMBER	No. of Pairs	AWG Size	Stranding	Nominal Insulation	Nominal Jacket	Nominal O.D.	Nominal Capacitance (pF/ft)	Weight Lbs/1000'
T5302	2	24	7	.015	.030	.226	12.5	25
T5303	3	24	7	.015	.030	.239	12.5	30
T5304	4	24	7	.015	.030	.262	12.5	36
T5320	5	24	7	.015	.030	.289	12.5	42
T5306	6	24	7	.015	.030	.297	12.5	47
T5308	7.5	24	7	.015	.030	.303	12.5	53
T5311	10	24	7	.015	.030	.369	12.5	70
T5313	12.5	24	7	.015	.030	.382	12.5	80
T5322	25	24	7	.015	.045	.530	12.5	160