

Hook-up & Lead Wire

UL1015, MTW, CSA TEW 600V 105°C Bare Copper

Conductor: Solid or Stranded Bare Copper
Insulation: PVC
Temperature Rating: 105°C
Operating Voltage: 600 Volts
Applications: Internal wiring of electrical or electronic equipment, panels, motor and transformer lead.
Approvals: UL AWM (Styles as noted), MTW, CSA AWM, TEW



TEVELEC NUMBER	AWG Size	Stranding	Nominal Insulation	Nominal O.D.	UL Style	Weight Lbs/1000'
T1058	18	16	.030	.108	UL1015/1230	9
T1062	16	26	.030	.121	UL1015/1230	13
T1066	14	41	.030	.131	UL1015/1230	19
T1069	12	65	.030	.153	UL1015/1230	29
T1073	10	105	.030	.182	UL1015/1230	42
T1075	8	165	.045	.259	UL1028/1231	70
T1076	6	266	.060	.333	UL1283/1232	117
T1077	4	133	.060	.390	UL1283/1232	176
T1042	4	413	.060	.390	UL1283/1232	176
T1078	2	259	.060	.455	UL1283/1232	262
T1043	2	665	.060	.460	UL1283/1232	265
T1079	1	259	.080	.500	UL1284/1232	345
T1080	1/0	1064	.080	.590	UL1284/1232	421
T1081	2/0	250	.080	.640	UL1284/1232	536
T1082	3/0	259	.080	.700	UL1284/1232	670
T1083	4/0	259	.080	.790	UL1284/1232	820
T1057	18	1	.030	.103	UL1015/1230	9
T1059	16	1	.030	.114	UL1015/1230	13
T1063	14	1	.030	.127	UL1015/1230	17
T1067	12	1	.030	.144	UL1015/1230	28
T1060	16	7	.030	.121	UL1015/1230	13
T1064	14	7	.030	.137	UL1015/1230	24
T1068	12	7	.030	.157	UL1015/1230	34
T1103	8	7	.045	.257	UL1028/1231	66
T1061	16	19	.030	.121	UL1015/1230	13
T1065	14	19	.030	.137	UL1015/1230	24
T1102	12	19	.030	.157	UL1015/1230	34
T1072	8	19	.045	.183	UL1028/1231	66

UL1284/1339/1346/10269 & UL CT Tray Rated, CSA AWM I A/B & TEW

Conductor: Stranded Bare Copper
Insulation: PVC
Temperature Rating: UL 1284/1339 105C 600V, UL10269 105C 1000V, CSA AWM I A/B & TEW 105C 600V
Operating Voltage: 600 Volts
Applications: Internal wiring of electrical or electronic equipment, internal wiring of panels and meters, motor and transformers.
Approvals: UL1284/1339 105C 600V, UL10269 105C 1000V, CSA AWM I A/B & TEW 105C 600V

TEVELEC	AWG	Stranding	Nominal	Nominal	UL	Weight
T1033	250	2421	.094	.835	1284/1339	978
T1034	350	3458	.100	1.045	1284/1339	1350
T1035	500	5054	.100	1.270	1284/1339	2929
T1036	750	7581	.115	1.380	1284/1339	2853