

# Multi-Paired Cable

## Individually Shielded Pairs UL CM, CSA CMG

**Conductors:** Tin-plated copper  
**Insulation:** Polyethylene  
**Shield:** Each pair shielded with aluminum/polyester foil facing out, one common 24 AWG tinned copper drain wire.  
**Jacket:** PVC  
**Construction:** Conductors paired and shielded. Shielded pairs cabled.  
**Temperature Rating:** 80°C  
**Color Code Chart:** Chart 10  
**Operating Voltage:** 300 Volts  
**Applications:** For interconnection of computers, analog audio and broadcast equipment, process control systems and similar applications requiring high isolation between pairs.  
**Approvals:** UL or CM, CSA CMG FT4



TEVELEC NUMBER	No. of Pairs	AWG Size	Stranding	Nominal Insulation	Nominal Jacket	Nominal O.D.	Weight Lbs/1000'
T3401	2	22	7	.010	.018	.165	20

**Conductors:** Tin-plated copper  
**Insulation:** Polyethylene  
**Shield:** aluminum/polyester foil shield, with 24 AWG tinned copper drain wire.  
**Jacket:** PVC  
**Construction:** Conductors paired, one pair shielded one pair unshielded. pairs cabled.  
**Temperature Rating:** 80°C  
**Color Code Chart:** Chart 10  
**Operating Voltage:** 300 Volts UL, 600 Volts CSA  
**Applications:** For interconnection of computers, analog audio and broadcast equipment, process control systems and similar applications requiring high isolation between pairs.  
**Approvals:** UL or CM, CSA CMG FT4



TEVELEC NUMBER	No. of Pairs	AWG Size	Stranding	Nominal Insulation	Nominal Jacket	Nominal O.D.	Weight Lbs/1000'
T6098	2	22	7	.010	.025	.185	30

**Conductors:** Tin-plated copper  
**Insulation:** Polyethylene  
**Shield:** Each pair aluminum/polyester foil shield, with 24 AWG tinned copper drain wire, and overall foil shield with 24 AWG tinned copper drain wire.  
**Jacket:** PVC  
**Construction:** Conductors paired, each pair shielded with 24 AWG tinned copper drain wire, pairs cabled, overall foil shield with 24 AWG tinned copper drain wire.  
**Temperature Rating:** 80°C  
**Color Code Chart:** Chart 10  
**Operating Voltage:** 300 Volts UL, 600 Volts CSA  
**Applications:** For interconnection of computers, analog audio and broadcast equipment, process control systems and similar applications requiring high isolation between pairs.  
**Approvals:** UL or CM, CSA CMG FT4



TEVELEC NUMBER	No. of Pairs	AWG Size	Stranding	Nominal Insulation	Nominal Jacket	Nominal O.D.	Weight Lbs/1000'
T3402	2	22	7	.010	.023	.222	33