

# Voice Communication Cable

## Station 'Z' Wire Solid Bare Copper

**Conductors:** Bare Copper Conductors  
**Insulation:** SR-PVC  
**Jacket:** PVC  
**Construction:** Insulated conductors cabled and jacketed.  
**Color Code Chart:** 7  
**Applications:** Used for wiring residential telephone lines (POTS), and for security control wiring in residential and commercial applications.  
**Approvals:** CSA CMG, FT4 60°C



TEVELEC NUMBER	No. of Conds.	AWG Size	Stranding	Nominal Insulation	Nominal Jacket	Nominal O.D.	Weight Lbs/1000'
T3992	2	22	Solid	.007	.018	.114	9
T3993	3	22	Solid	.007	.018	.120	12
T3994	4	22	Solid	.007	.020	.130	15

## JKTN Solid Bare Copper

**Conductors:** Bare Copper Conductors  
**Insulation:** SR-PVC  
**Jacket:** PVC  
**Construction:** Insulated conductors cabled and jacketed.  
**Color Code Chart:** 8  
**Applications:** Used for wiring small commercial telephone lines (POTS), and for security control wiring in residential and commercial applications, and for intercom and music systems.  
**Approvals:** CSA CMG, FT4 60°C



TEVELEC NUMBER	No. of Conds.	AWG Size	Stranding	Nominal Insulation	Nominal Jacket	Nominal O.D.	Weight Lbs/1000'
T3986	2	20	Solid	.010	.020	.151	17
T3987	3	20	Solid	.010	.020	.159	22
T3988	4	20	Solid	.010	.020	.173	27