


Data Communications Cable

Category 6 Armored PVC Jacketed Blue UTP 250 MHz


Conductors:	Solid bare copper
Insulation:	Polyolefin
Jacket:	Flame retardant PVC
Construction:	Conductors are paired
Temperature Rating:	105°C
Color Code Chart:	4R
Applications:	Data and voice applications and are ideal for installing in the ground, in ducts, tray and direct burial applications.
Approvals:	CSA CMG FT4



TEVELEC NUMBER	No. of Pairs	AWG Size	Stranding	Nominal Insulation	Nominal Jacket	Nominal O.D.	Weight Lbs/1000'
T6964AJ	4	23	Solid	.008	.245	.512	379
T6962AJ	8	23	Solid	.008	.245	.710	460

Category 6 Armored PVC Jacketed Blue Shielded 250 MHz

Conductors:	Solid bare copper
Insulation:	Polyolefin
Jacket:	Aluminum/Polyester Foil shield with 24AWG solid copper drain wire.
Construction:	Conductors are paired
Temperature Rating:	105°C
Color Code Chart:	4R
Applications:	Data and voice applications and are ideal for installing in the ground, in ducts, tray and direct burial applications.
Approvals:	CSA CMG FT4



TEVELEC NUMBER	No. of Pairs	AWG Size	Stranding	Nominal Insulation	Nominal Jacket	Nominal O.D.	Weight Lbs/1000'
T8364AJ	4	23	Solid	.008	.305	.550	414