

High Temperature Wire

Braided Silicone Rubber 600V 200°C, UL SF-2, CSA SEW-2

Conductor: Tin-Plated Copper
Insulation: Silicone Rubber, Glass Braid with High Temperature Saturant.
Temperature Rating: 200°C
Operating Voltage: 600 Volts
Applications: Internal wiring of electrical equipment.
Approvals: UL SF-2, UL AWM Styles as noted.
 CSA SEW-2



TEVELEC NUMBER	AWG Size	Stranding	Nominal Insulation	Nominal O.D.	UL Style	Weight Lbs/1000'
T1660	22	1	.030	.100	3172	7
T1661	20	1	.030	.107	3172	8
T1662	18	1	.030	.115	SF-2	10
T1663	16	1	.030	.126	SF-2	14
T1664	14	1	.030	.139	SF-2	20
T1665	12	1	.030	.156	3074	29
T1666	10	1	.045	.208	3075	48
T1672	18	7	.030	.124	SF-2	11
T1673	16	7	.030	.133	SF-2	15
T1674	14	7	.030	.147	SF-2	21
T1675	12	19	.030	.164	3074	29
T1676	10	19	.030	.218	3075	49
T1677	8	19	.045	.286	3231	84
T1678	6	19	.060	.326	3231	121
T1681	4	133	.060	.410	3231	178
T1682	2	259	.060	.480	3231	265
T1683	1	259	.060	.557	3231	346
T1684	1/0	259	.080	.595	3231	428
T1685	2/0	259	.080	.685	3231	525
T1686	3/0	259	.080	.740	3231	660
T1687	4/0	259	.080	.806	3231	795