

## Plenum Cable

### Multi-Conductor Shielded Overall Foil Shield

**Conductors:** Tinned or Bare Copper  
**Insulation:** Low smoke PVC  
**Shield:** Aluminum/polyester foil with 24 AWG tinned copper drain wire  
**Jacket:** Low Smoke PVC  
**Construction:** Conductors Cabled  
**Temperature Rating:** 75°C  
**Color Code Chart:** 1-12 conductors Chart 1, 13-25 conductors chart 2  
**Operating Voltage:** 300 Volts  
**Applications:** For use as computer cable, signaling, remote sensors, miniature control cable and sound system controls.  
**Approvals:** CMP FT6



TEVELEC NUMBER	No. of Conds.	AWG Size	Stranding	Nominal Insulation	Nominal Jacket	Nominal O.D.	Weight Lbs/1000'
T12603	3	24	7	.008	.013	.128	15
T12604	4	24	7	.008	.013	.150	18
T12606	6	24	7	.008	.013	.175	24
T12607	7	24	7	.008	.013	.185	27
T12608	8	24	7	.008	.013	.190	34
T12609	9	24	7	.008	.013	.200	38
T12610	10	24	7	.008	.013	.210	40
T12612	12	24	7	.008	.013	.230	47
T12615	15	24	7	.008	.013	.250	55
T12620	20	24	7	.008	.013	.270	67
T12625	25	24	7	.008	.013	.320	83

### Multi-Conductor Shielded Overall Foil Shield

**Conductors:** Bare Copper  
**Insulation:** Low smoke PVC  
**Shield:** Aluminum/polyester foil with 24 AWG tinned copper drain wire  
**Jacket:** Low Smoke PVC  
**Construction:** Conductors Cabled  
**Temperature Rating:** 75°C  
**Color Code Chart:** 1  
**Applications:** For use in signaling, remote sensors, miniature control cable and clock system controls.  
**Approvals:** CMP FT6



TEVELEC NUMBER	No. of Conds.	AWG Size	Stranding	Nominal Insulation	Nominal Jacket	Nominal O.D.	Weight Lbs/1000'
T13242	2	22	1	.008	.013	.127	8
T13244	4	22	1	.008	.013	.136	12